



SK125 TrailerTracker



The SK device range has been developed by Enigma Vehicle Systems Ltd, a UK based organisation, for use on the Skyline 7.0 remote asset tracking system. These are our 4th generation devices which draw upon many years of experience in the vehicle, plant security & fleet management business.

Skyline SK devices are available to integrators worldwide or partners who require a complete system to operate in their market. Please visit www.enigmavehicle.co.uk or call for further information.

The SK125TT has been designed as a specific trailer tracking solution. Depending on the reporting profile battery life can be 200+ days' (fully charged with twice daily wakeups). Our technical team can assist with customisation and configuration to your application requirements. As with all Skyline devices key parameters can be changed over the air.

Using an advanced high-sensitivity GPS & Quad-Band GSM modem the SK devices can operate globally provided GSM coverage is available.

System Requirements

Skyline is a web based application suitable for any Windows PC or Mac using either Internet Explorer or Mozilla (Firefox). It will work with other browsers although for best performance we recommend those named above.

Skyline PDA/ Smartphone –

Skyline will operate through a dedicated PDA web application and has been successfully used on iPhone, Blackberry, Nokia, Sony Ericsson and HTC. It provides many of the features available on the PC version including Google Satellite images, the ability to run reports and request current location. Skyline PDA puts mobility in your hands.

Feature	SK125TT
Model Number	VT10 SIM 340
USB Connection	•
Serial Port for Add-on features	•
Input Ports	4
Output Ports	4
Voice Function	x
GSM Modem	SIMCOM 2.5GHz (GSM/EGSM)
850/900/1800/1900 MHz GSM Module	•
66 Channel High Sensitivity GPS Receiver	•
Internal GPS Antenna (Auto-switch)	•
Internal GSM Antenna (Auto-switch)	x
GPS Cut Alert	•
GSM Cut Alert	x
Logging - Data Memory	100,000
Self-Defined Events	50 events
Pulse Counter	2
Battery	10A
Power Consumption @DC 3.7V with backup	<1 mA
Power Consumption @DC 12V with main	20 mA
Operating Temperature Range	-20°C to +55°C
Dimensions L x W x H in mm	190 x 115 x 50
Waterproof Case	•
Tracking by time, distance, direction	•
Journey Logging	•
Geo-Fence Setting	25
Speeding Report	•
Tow Away Report	•
Excessive Idle with voltage detection	•
Battery low warning alert	•
Periodic Timed Wake-up Reporting	•
Multiple Power Save Modes	•
Harsh Acceleration / Braking Detection	•
GPS Odometer Distance Accumulation	•
<ul style="list-style-type: none"> • Standard Feature □ Optional x Not Available 	



enigma vehicle systems

T +44 (0) 1702 507200 F +44 (0) 1702 511978 E info@enigmavehicle.co.uk
www.enigmavehicle.co.uk

